SCCSID = eaa\_canal\_profiles.man v1.1 02/15/03

Prepared by: Lehar Brion, Cary White

Date: 02/03/03

Hydrologic Systems Modeling Division

------

DRAFT DRAFT DRAFT DRAFT DRAFT DRAFT DRAFT

## SOUTH FLORIDA WATER MANAGEMENT MODEL V5.0 INPUT MAN PAGE FOR

> (unit no. 13) read in subroutine gen\_model\_def\_param\_data from source file gen\_model\_def\_param.F)

This file summarizes the HW-TW-STG relationships in the major EAA conveyance canals. These relationships were determined via backwater analysis using the water surface profile computer code HEC-2 for a practical range of tailwater and discharge combinations

\_\_\_\_\_\_\_

COLUMNS VARIABLE NAME			DESCRIPTION				
1. NUMBER OF CANAL REACHES: (1 record total)							
1-5	nreach will	I5 be define	number of EAA canal reaches where water surface profiles $\operatorname{cd}$ ; equal to nine (for now)				
note: Set of records 2 through 4 is read in nreach times.							
2. WATER SURFACE PROFILE DEFINITION: (1 record total)							
1-5 6-10 11-15	ireach ntws(ireach) n_eaaflows(ireach)	I5 I5 I5	reach number				
note: Set of records 3 and 4 is read in for $j = 1$ , ntws(ireach) times.							
3. DOWNSTREAM STAGE DATA: (1 record total)							
1-10	dsstage(j,ireach)	F10.0	canal downstream/tailwater stage (ft NGVD) for canal reach "ireach"				
note: Record 4 is read in for i = 1,n_eaaflows(ireach) times.							

4. DISCHARGE AND UPSTREAM STAGE DATA: (n\_eaaflows(ireach) records total)

\_\_\_\_\_\_

1-10	eaaflow(i,j,ireach)	F10.0	(steady-state) discharge (cfs)
11-20	usstage(i,j,ireach)	F10.0	canal upstream/headwater stage (ft NGVD) corresponding to
			(steady-state) discharge eaaflow(i,j,ireach) and canal
			downstream/tailwater stage dsstage(i ireach)

note: Typically, ireach = 1,2,3 and 4 are used for a no-STA simulation while ireach = 5,6,7,8 and 9 are used for a with-STA simulation.

note: Since the look-up table is monotonic, the 2-way interpolation routine associated with it expects dsstage() and usstage() to change (increase decrease) in the same direction as they are defined in this file.

## Additional notes:

Addictional in	les.		
The current	EAA reaches	defined in th	nis input file are:
ireach	upstream	downstream	description
1	S354_hw	S8_tw	canal reach along the Miami canal between S354 and S8 (about 26.2 miles long)
2	S351_hw	S7_tw	canal reach along the North New River canal between S351 and S7 (about 28.6 miles long)
3	S351_tw	S6_hw	canal reach along the Hillsboro canal between S351 and S6 (about 23.7 miles)
4	S352_tw	S5A_hw	canal reach along the West Palm Beach canal between S352 and S5A (about 20.8 miles long)
5	S354_tw	S8NEW_hw	canal reach along the upper Miami canal between S354 and location of STA diversion structure (referred to as S8NEW) (about 19.3 miles long)
6	S351_tw	S7NEW_hw	canal reach along the upper North New River canal between S351 and location of STA diversion structure (referred to as S7NEW) (about 24.6 miles long)
7	S351_tw	S6_hw	canal reach along the Hillsboro canal (with revised cross-sections) between S351 and S6 (about 23.7 miles long)
8	S8NEW_tw	S8_hw	canal reach along the lower Miami canal between location of STA diversion structure (referred to as S8NEW) and S8 (about 6.9 miles long)
9	S7NEW_tw	S7_hw	canal reach along the lower North New River canal between location of STA diversion structure (referred to as S7NEW) and S7

(about 4.0 miles long)